HK 60 VP/FT Hand-operated hydraulic crimping head 16 - 300 mm²



- **Suitable for crimping tubular cable lugs and connectors “standard type" and fine and superfine stranded conductors to 300 mm²**
- **The patented centring system guarantees optimum crimps every time**
- **Closed crimping head - ideal for utility lines construction**

Characteristics

- Quad-point indent crimping feature with patented centring system, no dies required
- Closed head with bolt interlock, rotatable, flip top style
- Light weight due to high quality aluminium housing
- 2-stage hydraulic system with fast feed and power stroke
- Simple and safe: Automatic retraction when operation is complete

Technical data	
Crimping force	55 kN
Crimping range	16 - 300 mm²
Length	535 mm
Weight	4.1 kg
Ambient temperature	-20 °C up to +40 °C

Item	Part-No.
Hand-operated hydraulic crimping tool 16 - 300 mm²	**HK60VPFT**

Scope of supply	Part-No.
Steel carrying case	MK60VP
Gauge and 10 test cylinder	TS10B

Accessories	Part.-No.
Gauge and 10 test cylinder	TS10B

Suitable for	Connection material	Crimping range mm²	Crimp profile
Copper tubular cable lugs and connectors			
Tubular cable lugs and connectors, standard type, tubular cable lugs for switchgear connections		16 - 300	
Tubular cable lugs and compression joints for fine stranded conductors		16 - 300	